



SMDJxxH Series 3000W Transient Voltage Suppressor


Rev.2.2

DESCRIPTION:

TVS diodes can be used in a wide range of applications which like consumer electronic products, automotive industries, munitions, telecommunications, aerospace industries, and intelligent control systems.

FEATURES:

- ✧ Low profile package.
- ✧ Low inductance.
- ✧ Excellent clamping capability.
- ✧ 3000W peak pulse power capability at 10/1000 μ s waveform.
- ✧ Typical I_R less than 5 μ A.
- ✧ Fast response time: typically less than 1.0ps from 0V to V_{BR} min.
- ✧ High temperature to reflow soldering: 260 $^{\circ}$ C/40s at terminals.
- ✧ Plastic package has underwriters laboratory flammability 94V-0.
- ✧ Meets MSL level 1, per J-STD-020, LF maximum peak of 260 $^{\circ}$ C.
- ✧ For surface mounted applications in order to optimize board space.
- ✧ Terminal: solder plated, solderable per J-STD-002.
- ✧ High reliability application and automotive grade (AEC-Q101 qualified).



SMC



Bi-directional



Uni-directional

Symbol

IEC COMPATIBILITY

- ✧ ISO16750-2 P5A 12V system (90V/4 Ω /200ms 10c)
- ✧ ISO16750-2 P5A 24V system (151V/8 Ω /200ms 10c)

ABSOLUTE MAXIMUM RATINGS($T_A=25^{\circ}$ C, RH=45%-75%, unless otherwise noted)


Parameter	Symbol	Value	Unit
Storage and operating junction temperature range	T_{STG}/T_J	-55 to +150	$^{\circ}$ C
Peak pulse power dissipation at 10/1000 μ s waveform	P_{PP}	3000	W
Steady state power dissipation at $T_L=75^{\circ}$ C	$P_{M(AV)}$	6.5	W
Maximum instantaneous forward voltage at 100A for unidirectional only	V_F	5.0	V
Peak forward surge current, 8.3ms single half sine wave(Note 1)	I_{FSM}	300	A
Typical thermal resistance junction to lead	$R_{\theta JL}$	15	$^{\circ}$ C/W

ABSOLUTE MAXIMUM RATINGS($T_A=25^{\circ}\text{C}$, RH=45%-75%, unless otherwise noted, continued)

Parameter	Symbol	Value	Unit
Typical thermal resistance junction to ambient	$R_{\theta JA}$	75	$^{\circ}\text{C/W}$

Notes:

1. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle=4 per minute maximum

MARKING

H12C: Device Marking Code
1409: In ninth week, 2014

ELECTRICAL CHARACTERISTICS($T_A=25^{\circ}\text{C}$)

Part Number		Marking		V_R	$I_R@V_R$	$V_{BR}@I_T$		I_T	$V_C@I_{PP}$	$I_{PP}^{①}$
Uni-Polar	Bi-Polar	Uni	Bi	V	μA	min(V)	max(V)	mA	max(V)	A
SMDJ12AH	SMDJ12CAH	H12A	H12C	12	5	13.30	14.70	5	19.9	150.8
SMDJ13AH	SMDJ13CAH	H13A	H13C	13	5	14.40	15.90	5	21.5	139.5
SMDJ14AH	SMDJ14CAH	H14A	H14C	14	5	15.60	17.20	5	23.2	129.3
SMDJ15AH	SMDJ15CAH	H15A	H15C	15	5	16.70	18.50	5	24.4	123.0
SMDJ16AH	SMDJ16CAH	H16A	H16C	16	5	17.80	19.70	5	26.0	115.4
SMDJ17AH	SMDJ17CAH	H17A	H17C	17	5	18.90	20.90	5	27.6	108.7
SMDJ18AH	SMDJ18CAH	H18A	H18C	18	5	20.00	22.20	5	29.2	102.7
SMDJ20AH	SMDJ20CAH	H20A	H20C	20	5	22.20	24.50	5	32.4	92.6
SMDJ22AH	SMDJ22CAH	H22A	H22C	22	5	24.40	26.90	5	35.5	84.5
SMDJ24AH	SMDJ24CAH	H24A	H24C	24	5	26.70	29.50	5	38.9	77.1
SMDJ26AH	SMDJ26CAH	H26A	H26C	26	5	28.90	31.90	5	42.1	71.3
SMDJ28AH	SMDJ28CAH	H28A	H28C	28	5	31.10	34.40	5	45.4	66.1
SMDJ30AH	SMDJ30CAH	H30A	H30C	30	5	33.30	36.80	5	48.4	62.0
SMDJ33AH	SMDJ33CAH	H33A	H33C	33	5	36.70	40.60	5	53.3	56.3
SMDJ36AH	SMDJ36CAH	H36A	H36C	36	5	40.00	44.20	5	58.1	51.6

ELECTRICAL CHARACTERISTICS($T_A=25^{\circ}\text{C}$, continued)

Part Number		Marking		V_R	$I_R@V_R$	$V_{BR}@I_T$		I_T	$V_C@I_{PP}$	$I_{PP}^{①}$
Uni-Polar	Bi-Polar	Uni	Bi	V	μA	min(V)	max(V)	mA	max(V)	A
SMDJ40AH	SMDJ40CAH	H40A	H40C	40	5	44.40	49.10	5	64.5	46.5
SMDJ43AH	SMDJ43CAH	H43A	H43C	43	5	47.80	52.80	5	69.4	43.2
SMDJ45AH	SMDJ45CAH	H45A	H45C	45	5	50.00	55.30	5	72.7	41.3
SMDJ48AH	SMDJ48CAH	H48A	H48C	48	5	53.30	58.90	5	77.4	38.8
SMDJ51AH	SMDJ51CAH	H51A	H51C	51	5	56.70	62.70	5	82.4	36.4
SMDJ54AH	SMDJ54CAH	H54A	H54C	54	5	60.00	66.30	1	87.1	34.4

① Surge waveform: 10/1000 μs V_R : Stand-off voltage -- Maximum voltage that can be applied V_{BR} : Breakdown voltage V_C : Clamping voltage -- Peak voltage measured across the suppressor at a specified I_{PP} I_R : Reverse leakage current**ORDERING INFORMATION**

SMDJ	xx	C	A	H
3000W SMC Series	V_R Voltage	C: Bi-directional	5% V_{BR} Voltage tolerance	For AEC-Q101



RATINGS AND V-I CHARACTERISTICS CURVES ($T_A=25^{\circ}\text{C}$, unless otherwise noted)**FIG.1:V- I curve characteristics**
(Uni-directional)**FIG.2:V- I curve characteristics**
(Bi-directional)

FIG.3: Pulse waveform




FIG.4: Pulse derating curve




FIG.5: ISO16750 -2 test pulse 5A





FIG.6: Parameters for test pulse 5a


Parameter	12V system	24V system
Us	79V to 101V	151V to 202V
Ri	0.5Ω to 4Ω	1 Ω to 8Ω
td	40ms to 400ms	100ms to 350ms
tr	5-10ms	5-10ms

SOLDERING PARAMETERS

Reflow Condition		Pb-Free assembly (see figure at right)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150°C
	-Temperature Max($T_{s(max)}$)	+200°C
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquidus Temp (T_L)to peak)		3°C/sec. Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/sec. Max
Reflow	-Temperature(T_L)(Liquidus)	+217°C
	-Temperature(t_L)	60-150 secs.
Peak Temp (T_P)		+260(+0/-5)°C
Time within 5°C of actual Peak Temp (t_P)		20-40secs.
Ramp-down Rate		6°C/sec. Max
Time 25°C to Peak Temp (T_P)		8 min. Max
Do not exceed		+260°C




PACKAGE MECHANICAL DATA



Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	5.75	6.25	0.226	0.246
B	6.90	7.40	0.272	0.291
C	2.75	3.25	0.108	0.128
D	0.95	1.52	0.037	0.060
E	7.70	8.20	0.303	0.323
F	0.051	0.203	0.002	0.008
G	0.15	0.31	0.006	0.012
H	2.15	2.62	0.085	0.103
J	2.40		0.094	
K		4.20		0.165
L	3.30		0.130	

TAPE AND REEL SPECIFICATION-SMC



Ref.	Dimensions	
	Millimeters	Inches
A0	6.05 ± 0.3	0.238 ± 0.012
B0	8.31 ± 0.3	0.327 ± 0.012
C	330.0	13.0
D0	1.55 ± 0.1	0.061 ± 0.004
E	1.75 ± 0.2	0.069 ± 0.008
E1	13.3 ± 0.3	0.524 ± 0.012
F	7.50 ± 0.2	0.295 ± 0.008
P0	4.00 ± 0.2	0.157 ± 0.008
P1	8.00 ± 0.2	0.3145 ± 0.008
P2	2.00 ± 0.2	0.079 ± 0.008
W	16.0 ± 0.2	0.630 ± 0.008
W1	19.7 ± 2.0	0.776 ± 0.079

PART No.	UNIT WEIGHT (g/PCS) typ.	REEL (PCS)	PER CARTON (PCS)	DESCRIPTION
SMDJxxAH/CAH	0.31	3,000	48,000	13 inch reel pack

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 2.2nd version which is made in 28-Sept.-2019. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.

Copyright©2019 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.
